

ASPTouch 90™

Economical Fixed Barcode Scanning



Are you looking for a low cost, entry level corded USB barcode scanner that doesn't compromise on scanning performance?

The ASPTouch 90™ is the scanner for you.

With proprietary barcode decoding technology and 200 scans per second, and weighing just 100 grams but able to withstand 1.5 metre drops, the ASPTouch 90™ combines great performance with excellent robustness and durability.

SPECIFICATIONS	
ELECTRICAL	
System interface	USB
Input Voltage	5 VDC ± 10%
Operating Current	110mA typical
OPERATIONAL	
Light Source	630nm visible red LED
Optical System	Linear CCD array
Microprocessor	32 bit
Depth of Field	0-20 mm (UPC/EAN 100%, PSC=90%)
Scan Rate	200 scans per second
Minimum Bar Width	0.1 mm (4 mil) (Code 39, PCS=90%, contact)
Print Contrast	Min. 30% @ UPC/EAN 100%
Indicators (LED)	Blue LED
Beeper Operation	Programmable tone and beep time
PHYSICAL	
Dimensions	171.3 x 91.1 x 63.0 mm (handheld only)
Weight	100 g
Cable Length	2 metre straight
REGULATORY	
EMC	CTick, CE & FCC compliant
SYMBOLGY	
All UPC/EAN/JAN, EAN 128 Code, Code 128, Code 39, Code 39 Full ASCII, CODABAR/NW7, Interleaved 2 of 5	
ENVIRONMENT	
Operating Temperature	0°C to 50°C
Storage temperature	-20°C to 60°C
Humidity	5% - 95% RH (non condensing)
Ambient Light Injection	Max. 4,500 LUX
Shock	Designed to withstand 1.5m drops

- Perfectly suited to Retail and general purpose applications
- Backed by a 12 month warranty
- Lightweight and ergonomic
- Blue beam indicator to identify good scan
- Ergonomic centered trigger
- Quick and easy to install
- Low power USB connectivity



Our Innovation - Your Edge™

ASP MICROCOMPUTERS 456 North Road, ORMOND VIC 3204

T: 03 9578 7600 F: 03 9578 7727 Toll Free 1800 061 642

E: solutions@asp.com.au W: www.asp.com.au

ASPTouch 90 is a Trademark of ASP Microcomputers
Specifications subject to change without notice (E&OE) 0211

