

CN3/CN3e



CN4/CN4e



CN50



CK3B



CK31/CK31ex



CK32IS



CK61/CK61ex



Primary Applications	Field Service; DSD Route Sales; LTL; Courier Express; Postal Vehicle; Airline Baggage & Cargo; Hazardous Environments	Field Service; DSD Route Sales; LTL; Courier Express; Postal Vehicle; Airline Baggage & Cargo; Hazardous Environments	Merchandising/Presales Postal "hold and carry" Courier & Express Parcels Home Healthcare Hospitality	In-premise Retail Industrial Distribution	Retail Industrial Distribution	Hazardous Environments	Industrial Distribution Field Service
Durability	1.8m drops per MIL-STD 810G; CN3 - IP54, CN3e - IP64	1.8m drops per MIL-STD 810G; IP64	1.5m drops per MIL-STD 810G; IP54	1.5m drops per MIL-STD 810G; IP54	1.8m drops per MIL-STD 810G; IP64	1.5m drops per MIL-STD 810G; IP67; ATEX zone 0	1.8m drops per MIL-STD 810G; IP64
Operating System	Windows Mobile 5.0 Windows Mobile 6.1	Windows Mobile 6.1	Windows Mobile 6.1	Windows Mobile 6.1 Classic Edition	Windows CE .NET 4.2	Windows Mobile 5.0	Windows Mobile 5.0 Windows CE 5.0
Application Development	Embedded Visual C++ 4.0, Visual Studio, .NET Eclipse Compact Framework (VB .NET & C#) Optional TE	Embedded Visual C++ 4.0, Visual Studio, .NET Eclipse Compact Framework (VB .NET & C#) Optional TE	Visual Studio (2005/2008) Eclipse, .NET Compact Framework	Embedded Visual C++ 4.0, .NET Compact Framework (VB .NET & C#) Optional Terminal Emulation ITE	Embedded Visual C++ 4.0, .NET Compact Framework (VB .NET & C# TE) Optional Terminal Emulation ITE	Embedded Visual C++ 4.0, .NET Compact Framework (VB .NET & C#) Optional Terminal Emulation ITE	Embedded Visual C++ 4.0, .NET Compact Framework (VB .NET & C#)
Display	3.5" QVGA color, touch	3.5" QVGA color, touch	3.5" QVGA color, touch, embedded Accelerometer	3.5" QVGA color, touch	3.5" QVGA color, touch	3.5" QVGA color, touch	3.8" QVGA color, touch
Memory/Storage	128 MB RAM 256 MB Flash	128 MB RAM 256 MB Flash	up to 256 MB RAM 512 MB Flash	128 MB RAM 512 MB Flash	64 MB RAM 64 MB Flash	128 MB RAM 64 MB Flash 512 MB embedded SD Flash	128 MB RAM 192 MB Flash
Scanner Options	2.0 MP Color Camera Area Imager	2.0MP color camera OR Area Imager Supports Enhanced Mobile Document Imaging	3.1MP color camera & Area Imager (both standard) Supports Enhanced Mobile Document Imaging	Linear Imager 2D Area Imager 2D Near-Far Area Imager	CK31 - Linear Imager Area Imager CK31ex - 2D Near-Far Area Imager	Linear Imager	Linear Imager Area Imager CK61ex - 2D Near-Far Area Imager
Radio Type Options	802.11 b/g Bluetooth® Cisco® Compatible CCX GSM/GPRS/EDGE or CDMA/1xRTT/EV-DO Integrated GPS	802.11 b/g Bluetooth® 2.0 + EDR Cisco® Compatible CCX v.4 GSM/GPRS/EDGE/ UMTS/HSDPA Integrated GPS	801.11 b/g with WPA/WPA2 Bluetooth 2.0 + EDR GSM/GPRS/EDGE/UMTS/ HSDPA-HSUPA Integrated GPS or GSM/GPRS/EDGE	802.11 a/b/g Bluetooth® v2.0+EDR Cisco® Compatible CCX	802.11 b/g Bluetooth® Cisco® Compatible CCX	802.11 b/g Bluetooth® Cisco® Compatible CCX	802.11 a/b/g Bluetooth® Cisco® Compatible CCX