

Bar Code Hang Tag

Affix a label directly to an asset where it won't adhere

The **Bar Code Hang Tag** is perfect for tracking applications where you normally wouldn't be able to affix a label directly to an asset or where the cold temperature prevents the adhesive to perform properly. A removable, reusable solution for a variety of applications. The **Bar Code Hang Tag** may be used for cold storage, asset control, personnel identification, logistics, work-in-progress, warehousing applications and more.



The thick tag is a clear 0.08 mm (0.003") polyester construction laminated to 0.25 mm (0.010") white polyester, which keeps the contour of the tag thin, yet offers excellent sterness and resistance to protect the tag from being bent and torn. With the open tab the tag does not need to be permanently affixed to assets and can be easily attached and removed by using plastic strips to attach to the application. Subsurface printing provides an added layer of protection for logos, copy, and bar code from moderate solvents, caustics, acids and moderate abrasion. Our digital four colour printing process and double sided registration ensures even the most detailed logo will look crisp and clean allowing you to show off and promote your company on this premium tag.

Custom colours are also available at no additional charge.



Test Results






These tests were conducted for a limited period of time in strict laboratory conditions. In order to achieve maximum satisfaction we highly recommend that any customer considering use of this product test the labels in the environment in which they will be used.

Chemical Soak Test Results

Length of Immersion	Water	Glass Cleaner	Bathroom Cleaner pH 10.0	Isop. Alcohol 99%	Acetone 100%	NaOH pH 12.0	HNO3 pH 1.0	HCl pH 1.0	Brake Fluid	Diesel Fuel
2 Hours	N.E.	N.E.	N.E.	Slight Adhesive Ooze	Some Adhesive Ooze	N.E.	N.E.	N.E.	N.E.	N.E.
24 Hours	N.E.	N.E.	N.E.	Edges Loosened	Severe Delamination	N.E.	N.E.	N.E.	N.E.	N.E.

N.E. = No Effect

SPECIFICATIONS

Construction	0.08 mm (0.003") thick clear polyester laminated to 0.25 mm (0.010") thick white polyester.
Label Copy	The label copy may include block type, stylised type, logos or other designs. All copy, block type, stylised type, logos, designs, and bar code are subsurface printed. This unique process provides excellent resistance to solvents, caustics, acids and moderate abrasion.
Standard Sizes	120 mm x 44 mm (4-3/4" x 1-3/4"), 52 mm x 38mm (2.0" x 1-1/2")
Affixing Methods	Various mechanical fasteners (i.e., plastic cable ties and wire attachments)
Colours	Standard colours include black, red, yellow, green and blue. Custom spot colours also available at no additional charge. All bar codes are imaged in black only, due to contrast needed for the bar code scanner. <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;"> BLACK</div> <div style="text-align: center;"> BLUE</div> <div style="text-align: center;"> RED</div> <div style="text-align: center;"> GREEN</div> <div style="text-align: center;"> YELLOW</div> </div>
Serialisation	Bar code and human readable equivalent is produced using the latest high resolution digital technology available, which provides excellent clarity and easy scanning. Code 39 is the standard symbology with a range of 2.7 to 9.4 CPI (characters per inch). <i>Optional symbology</i> include Code 128, I 2 of 5, 2D Data Matrix and QR Code. This product is also available with human readable numbers only or with static copy

- **Variable copy available**
- **Construction doesn't require tag to be affixed directly to the asset**
- **Available with choice of 1, 2, 3 or 4 colours including spot colours and 4 colour process**
- **Digital printing process provides for greater print capability with detailed logos or special designs**
- **Thin profile, but with construction rigid enough that resists bending and tearing**
- **Double sided registration available**



Our Innovation - Your Edge™

ASP MICROCOMPUTERS
14 Business Park Drive, Notting Hill, VIC 3168
T: 03 9578 7600 F: 03 9578 7727 Toll Free 1800 061 642
E: solutions@asp.com.au W: www.asp.com.au

Specifications subject to change without notice (E&OE) 0320

